



A budget over head door closer for general applications.





All dimensions in mm.

BS EN 1154 Classification

TS2204 door closers have been independently tested to conform with the EN 1154 performance standard. They are CE marked and classified as follows:

Standard Arm Fig 1

BS EN 1634 Fire Test

TS2204 closers have been tested to EN 1634 at power size 3 for 30 and 60 minute door sets. Test certificates are available on request.

Product Specification

Power size (adjustable by position)

EN3 Mechanism Rack and Pinion Adjustable closing speed (2 speeds) Yes Max door width (mm) Max door weight (kg) Opening angle LH and RH doors - universal application Available finishes Yes Silver and Gold	,	
Adjustable closing speed (2 speeds) Max door width (mm) 950 Max door weight (kg) Opening angle LH and RH doors - universal application Yes	EN3	Yes
Max door width (mm) 950 Max door weight (kg) 60 Opening angle 105° LH and RH doors - universal application Yes	Mechanism	Rack and Pinion
Max door weight (kg) 60 Opening angle 105° LH and RH doors - universal application Yes	Adjustable closing speed (2 speeds)	Yes
Opening angle 105° LH and RH doors - universal application Yes	Max door width (mm)	950
LH and RH doors - universal application Yes	Max door weight (kg)	60
	Opening angle	105°
Available finishes Silver and Gold	LH and RH doors - universal application	Yes
	Available finishes	Silver and Gold

Note: Parallel arm bracket also included

Options

Square Covers Range of finishes



